

Battle Spec Helmet

Remove decals from printed sheet and plant them on the spaces indicated.

The brow trim provided needs cutting back to fit.



There are two predrilled holes in the back and front of the helmet

Fix the helmet together using M3 x 10mm screws and nuts



With the centre screw fixed you can now adjust the attitude of the brow. High brow for Stunt and low brow for Hero

When you have decided your brow position drill a 3mm hole in the valley by the cheek and fix with M3 screw and nut.

Repeat this on the other side of the helmet.



The earpieces are roughly marked out with a pencil line, but check continually the fit of the ear to the helmet before trimming as far as this pencil line.

Depending on where the brow position is set, the ear will adopt a different final trim.



Battle Spec helmet

The heavy rubber trim is used around neck. Starting from the centre of the back, install the trim and work it around the periphery until it meets at the back.



Cut the trim with heavy scissors slightly longer so that it will press tightly together.



Trim the mouth piece moulding to simulate the painted mouth of screen used helmets. Glue the mouthpiece with hot melt glue



The mic tips are already assembled and can be glued in position with hot melt glue.

The green lens for the eyes is an Acetate sheet that attaches to the same screws that hold the ears on. Mark the hole position by looking through the Acetate to the screw head beneath.



Finally cover the screw heads with the adhesive backed Polyethylene foam and insert the leaf shaped foam head piece.